



中国建材

[www.zfsycf.com.cn](http://www.zfsycf.com.cn)

## ZHONGFU SHENYING CARBON FIBER

### Product & Packaging chart



[www.zfeurope.eu](http://www.zfeurope.eu)

revised date : April, 2020

MODEL	TOW	Tensile strenght	Modulus	Elongation	linear density/dtex	density g/cm <sup>3</sup>	filament diameter	bobbin weight /kg	bobbins /box	box weight /kg	boxes /pallet	pallet weight /kg
SYT45S	3K	4000	230	1,7	198	1,79	7	1	15	15	36	540
	12K	4500	230	1,8	800	1,79	7	4	6	24	36	864
	24K	4500	230	1,8	1600	1,79	7	6	6	36	30	1080
SYT49S	12K	4900	230	2,1	800	1,79	7	4	6	24	36	864
	24K	4900	230	2,1	1600	1,79	7	6	6	36	30	1080
SYM30	12K	4900	290	1,6	740	1,7	7	3,7	6	22,2	36	799,2
SYM35	12K	4900	340	1,4	450	1,72	5	2	12	24	36	864
SYM40	12K	4700	375	1,2	430	1,78	5	0,7	15	10,5	36	378
SYT55	12K	5500	290	1,8	450	1,79	5	2	12	24	36	864
SYT55S	12K	5900	295	1,9	450	1,79	5	1/2	15/12	15/24	36	540/864

ZHONGFU-SHENYING CARBON FIBRE Co. Ltd EUROPEAN REPRESENTATIVE  
NADALIA CONSULTING di Nadia Bosis  
[nadiabosis@nadalia.it](mailto:nadiabosis@nadalia.it) [www.nadalia.it](http://www.nadalia.it)  
mobile +39 3286577284

**NADALIA**  
CONSULTING